



## Galaxyit

- The touch switches on the pole allows stepless adjustment of the brightness and color temperature and the switching on/off of the light.
- Strong indirect illumination and soft effect light on the rim of the flange.
- High energy efficiency for an elegant and economical product.
- Glare-free, pleasant and homogeneous light distribution.
- 5 years warranty.



### Technical data

Power:	45 W
Weighted energy consumption:	45 kWh / 1000 h
Voltage:	AC 200–240 V, 50–60 Hz
Luminous flux:	5400 Lumen
Luminous efficacy:	120 Lumen / Watt
Colour temperature:	3000~5700 Kelvin (stepless variable) max. 3 MacAdam ellipses
Colour rendering index (CRI):	> 80
UGR (Unified Glare Rating):	< 10
Life time:	50 000 hours (L 80)
Height:	1900 mm
Base:	240 x 8 mm (Ø x H)
Head of lamp:	298 x 28 mm (Ø x H)
Pole:	Ø 30 mm upper part, Ø 60 mm lower part
Length of the cable:	2.0 m, socket on the pole
Net weight:	6.5 kg
Material:	aluminium, steel, PS, PMMA
Packaging:	white packaging with coloured label 1 parcel: 197 x 43 x 12.6 cm, 10.9 kg, girth: 308.2 cm
Light sources:	Energy efficiency class: D (indirect) / D (flange)
Model identifiers:	galax0001080x (indirect) / galax0002080x (flange)

**Item number:** **41-5010.800.CH white**  
**41-5010.801.CH black**

### Interchangeability

The lighting source cannot be replaced. The construction of the luminaire does not allow the lighting source to be replaced, as there is a risk of damaging the luminaire.

**styro ag**  
Frauholzstrasse 27  
CH-6422 Steinen  
www.styro.ch