



LED Topas CCT

- The touch dimmer on the pole allows stepless adjustment of the light intensity and light colour as well as switching the light on and off.
- Direct (ca. 25%) and indirect (ca. 75%) illumination can be operated independently of each other.
- The optimised reflector and glare shield guarantees a pleasant and homogeneous light distribution on the work surface and avoids disturbing glare.
- Motion sensor: after 30 minutes absence the brightness reduces to 30%, after another 30 minutes the luminaire automatically switches off.
- Thanks to the daylight sensor, the brightness on the work area is recorded and the light intensity is adjusted according to the ambient light.
- 5 years warranty



Technical data

Power:	80 W
Weighted energy consumption:	80 kWh / 1000 h
Voltage:	200–240 V AC, 50–60 Hz
Luminous flux:	7600 Lumen, 2100 lm direct, 5500 lm indirect
Luminous efficacy:	95 Lumen / Watt
Colour temperature:	3000–6000 Kelvin (adjustable) max. 3 MacAdam ellipses
Maximum illuminance:	1300 Lux (measuring distance 120 cm)
Colour rendering index (CRI):	> 80
UGR (Unified Glare Rating):	< 15
Life time:	50 000 hours
Height:	1960 mm
Base:	580 mm x 335 mm (L x W)
Head of lamp:	1203 mm x 52 mm x 36 mm (L x W x H)
Length of the cable:	2.5 m
Net weight:	12.1 kg
Material:	aluminium, steel, PS, PMMA
Packaging:	white packaging with coloured label 1 parcel: 204 x 23 x 16 cm, 14.6 kg, girth: 282 cm
Light source:	energy efficiency class: E model identification: topas0000172x

Item number: **41-5010.722.CH white**
41-5010.723.CH anthracite

Interchangeability

The lighting source cannot be replaced. The construction of the luminaire does not allow the lighting source to be replaced, as there is a risk of damaging the luminaire.

styro ag
Frauholzstrasse 27
CH-6422 Steinen
www.styro.ch



LED Topas

- The touch dimmer on the pole allows stepless adjustment of the light intensity and switching the light on and off.
- Direct (ca. 25%) and indirect (ca. 75%) illumination can be operated independently of each other.
- The optimised reflector and glare shield guarantees a pleasant and homogeneous light distribution on the work surface and avoids disturbing glare.
- Motion sensor: after 30 minutes absence the brightness reduces to 30%, after another 30 minutes the luminaire automatically switches off.
- Thanks to the daylight sensor, the brightness on the work area is recorded and the light intensity is adjusted according to the ambient light.
- 5 years warranty



Technical data

Power:	80 W
Weighted energy consumption:	80 kWh / 1000 h
Voltage:	200 – 240 V AC, 50 – 60 Hz
Luminous flux:	9300 Lumen, 2600 lm direct, 6700 lm indirect
Luminous efficacy:	116 Lumen / Watt
Colour temperature:	4000 Kelvin (neutral white), max. 3 MacAdam ellipses
Maximum illuminance:	1300 Lux (measuring distance 120 cm)
Colour rendering index (CRI):	> 80
UGR (Unified Glare Rating):	< 15
Life time:	50 000 hours
Height:	1960 mm
Base:	580 mm x 335 mm (L x W)
Head of lamp:	1203 mm x 52 mm x 36 mm (L x W x H)
Length of the cable:	2.5 m
Net weight:	12.1 kg
Material:	aluminium, steel, PS, PMMA
Packaging:	white packaging with coloured label
Light source:	1 parcel: 204 x 23 x 16 cm, 14.6 kg, girth: 282 cm energy efficiency class: C model identification: topas0000072x

Item number: **41-5010.720.CH white**
41-5010.721.CH anthracite

Interchangeability

The lighting source cannot be replaced. The construction of the luminaire does not allow the lighting source to be replaced, as there is a risk of damaging the luminaire.

Data verification

Electrical and photometric data checked by the lighting lab of the University of Applied Sciences of the Grisons, Switzerland.

styro ag
Frauholzstrasse 27
CH-6422 Steinen
www.styro.ch