

## LED Alu Connect

- LED ceiling lamp for direct ceiling mounting or suitable as a suspension lamp; steel wire suspension kit included
- With the included remote control the brightness and color temperature can be steplessly adjusted; with memory function
- A lamp can be controlled individually or as part of a group (3 channels / groups on remote control available), range up to 30 m
- Multiple ceiling lamps can be connected in series



### Technical data

Power:	36 W
Weighted energy consumption:	36 kWh / 1000 h
Voltage:	110 – 240 V AC, 50 – 60 Hz
Luminous flux:	2800 Lumen
Luminous efficacy:	78 Lumen / Watt
Colour temperature:	3100 – 7000 Kelvin
Maximum illuminance:	620 Lux (measuring distance 110 cm) 275 Lux (measuring distance 165 cm)
Colour rendering index (CRI):	> 80
Life time:	20 000 hours
Dimensions:	118 cm x 11 cm x 6 cm (L x W x H)
Net weight:	1700 g
Remote control:	range up to 30 m, batteries not included
Cable length:	transparent, 2,0 m
Steel wire suspension:	1,50 m
Material:	aluminium, ABS, PC, steel
Packaging:	white packaging with colour label
Protection class:	1
Degree of protection:	IP20
Light source:	energy efficiency class: E model identification: aluco00000700

**Item number:** 41-5010.700 silver

### **Interchangeability**

The lighting source cannot be replaced. The construction of the luminaire does not allow the lighting source to be replaced, as there is a risk of damaging the luminaire.

### **Data verification**

Electrical and photometric data checked by the lighting lab of the University of Applied Sciences of the Grisons, Switzerland.



**styro ag**  
Frauholzstrasse 27  
CH-6422 Steinen  
www.styro.ch