



LED Beryll

- Professional LED floor luminaire in a fine, modern design
- Ideal direct and indirect illumination:
52% direct light / 48% indirect light
- Long lamp head for precise illumination of the work surface
- ON/OFF switch at lamp head
- Microprismatic diffuser avoids disturbing glare
- Easy and fast to assemble
- 5 years warranty



Technical data

Power:	50 W
Weighted energy consumption:	50 kWh / 1000 h
Voltage:	200 – 240 V AC, 50 Hz
Luminous flux:	3970 Lumen, 2070 lm direct, 1900 lm indirect
Luminous efficacy:	83 Lumen / Watt
Colour temperature:	4200 Kelvin (neutral white), max. 3 MacAdam ellipses
Maximum illuminance:	1080 Lux (measuring distance 105 cm)
Colour rendering index (CRI):	> 80
Life time:	50 000 hours
Height:	1800 mm
Base:	450 mm x 180 mm (L x W)
Head of lamp:	984 mm x 65 mm x 35 mm (L x W x H)
Length of the cable:	2.0 m
Net weight:	6.95 kg
Material:	aluminium, iron, PS, PC
Packaging:	white packaging with color label 1 parcel: 185 x 23 x 10 cm, 8.5 kg, girth: 251 cm
Light source:	energy efficiency class: D model identification: beryll0000070x

Item number: **41-5010.705.CH white**
41-5010.706.CH black

Interchangeability

The lighting source cannot be replaced. The construction of the luminaire does not allow the lighting source to be replaced, as there is a risk of damaging the luminaire.

Data verification

Electrical and photometric data checked by the lighting lab of the University of Applied Sciences of the Grisons, Switzerland.



styro ag
Frauholzstrasse 27
CH-6422 Steinen
www.styro.ch