



Onyx

- The rocker switch on the pole allows stepless adjustment of the light intensity and the switching on/off of the light.
- Strong indirect illumination and soft effect light on the rim of the flange.
- High energy efficiency for an elegant and economical product.
- Glare-free, pleasant and homogeneous light distribution.
- 5 years warranty.



Technical data

Power:	45 W
Weighted energy consumption:	45 kWh / 1000 h
Voltage:	AC 200–240 V, 50–60 Hz
Luminous flux:	5400 Lumen
Luminous efficacy:	120 Lumen / Watt
Colour temperature:	4000 Kelvin (neutral white), max. 3 MacAdam ellipses
Colour rendering index (CRI):	> 80
UGR (Unified Glare Rating):	< 10
Life time:	50 000 hours (L 80)
Stand-by power:	< 0.5 W
Height:	1901 mm
Base:	240 x 240 x 8 mm (L x W x H)
Head of lamp:	298 x 298 x 24 mm (L x W x H)
Pole:	28 x 28 mm upper part, 52 x 52 mm lower part
Length of the cable:	2.0 m, socket on the pole
Net weight:	7.1 kg
Material:	aluminium, steel, PS, PMMA
Packaging:	white packaging with coloured label
	1 parcel: 197 x 43 x 12.6 cm, 11.4 kg, girth: 308.2 cm
Light sources:	Energy efficiency class: D (indirect) / D (flange)
Model identifiers:	onyx00001080x (indirect) / onyx00002080x (flange)

Item number: **41-5010.802.CH white**
41-5010.803.CH black

Interchangeability

The lighting source cannot be replaced. The construction of the luminaire does not allow the lighting source to be replaced, as there is a risk of damaging the luminaire.

styro ag
Frauholzstrasse 27
CH-6422 Steinen
www.styro.ch